










## Modellstorlekar

| TYP                       | 1.06  | 1.08  | 1.10  | 1.12  | 1.16  | 1.20   | 2.10  | 2.14  | 2.20  |
|---------------------------|---|---|---|---|---|--|---|---|---|
|                           |  |  |  |  |  |  |  |  |  |
| <b>KAPACITET</b>          |   |   |   |   |   |  |   |   |   |
| Kantinstorlek             | 1/1 GN eller 400 x 600 mm   | 1/1 GN eller 400 x 600 mm   | 1/1 GN eller 400 x 600 mm   | 1/1 GN eller 400 x 600 mm   | 1/1 GN eller 400 x 600 mm   | 1/1 GN eller 400 x 600 mm  | 2/1 GN eller 1/1 GN   | 2/1 GN eller 1/1 GN   | 2/1 GN eller 1/1 GN   |
| Antal gejder, 65 mm       | 6   | 8   | 10  | 12  | 16  | 20   | 10 (20)   | 14 (28)   | 20 (40)   |
| Antal gejder, 85 mm       | 5   | 7*  | 8   | 10*   | 12  | 15   | 8 (16)  | 11 (22)   | 15 (30)   |
| Antal personer            | 90  | 120   | 150   | 180   | 240   | 300  | 300   | 420   | 600   |
| Potatis                   | 24/20 kg  | 32/25 kg  | 40/32 kg  | 48/38 kg  | 64/51 kg  | 80/64 kg   | 80/64 kg  | 112/89 kg   | 160/128 kg  |
| Ris                       | 6 kg  | 8 kg  | 10 kg   | 12 kg   | 16 kg   | 20 kg  | 20 kg   | 28 kg   | 40 kg   |
| Grönsaker                 | 15 kg   | 20 kg   | 25 kg   | 30 kg   | 40 kg   | 50 kg  | 50 kg   | 70 kg   | 100 kg  |
| Stek                      | 18-21 kg  | 24-28 kg  | 30-35 kg  | 36-42 kg  | 48-56 kg  | 60-70 kg   | 60-70 kg  | 84-96 kg  | 120-140 kg  |
| Kycklingar, 900 gr        | 16 st   | 16 st   | 24 st   | 32 st   | 40 st   | 48 st  | 48 st   | 64 st   | 96 st   |
| Frallor                   | Antal per 1/1 GN plät: 15 st  |   |   |   |   |  |   |   |   |
| <b>SPECIFIKATIONER</b>    |   |   |   |   |   |  |   |   |   |
| El-spänning**             | 400V AC 3N + E  |   |   |   |   |  |   |   |   |
| Anslutningseffekt         | 9 kW  | 18 kW   | 18 kW   | 18 kW   | 24 kW   | 36 kW  | 27 kW   | 27 kW   | 60 kW   |
| Strömförbrukning          | 13 A  | 26 A  | 26 A  | 26 A  | 35 A  | 52 A   | 39 A  | 39 A  | 88 A  |
| Vattenanslutning          | 3/4" RG utvändig gänga (avhärdat vatten)  |   |   |   |   |  |   |   |   |
| Avlopp                    | Ø 50 mm utvändig  |   |   |   |   |  |   |   |   |
| Temperaturområde          | 30 - 250°C (möjlighet till förvärmning 300°C)                                     |   |   |   |   |  |   |   |   |
| <b>DIMENSIONER + VIKT</b> |   |   |   |   |   |  |   |   |   |
| Bredd                     | 900 mm  | 900 mm  | 900 mm  | 900 mm  | 900 mm  | 900 mm   | 1125 mm   | 1125 mm   | 1125 mm   |
| Höjd bordsmodell          | 795 mm  | 925 mm  | 1055 mm   | 1185 mm   |   |  |   |   |   |
| Höjd med stativ           | 1495 mm   | 1495 mm   | 1495 mm   | 1495 mm   | 1595 mm   | 1855 mm  | 1495 mm   | 1495 mm   | 1855 mm   |
| Djup (exkl. handtag)      | 831 mm  | 831 mm  | 831 mm  | 831 mm  | 886 mm  | 886 mm   | 951 mm  | 951 mm  | 1004 mm   |
| Vikt                      | 150 kg  | 170 kg  | 190 kg  | 210 kg  | 240 kg  | 270 kg   | 230 kg  | 250 kg  | 370 kg  |

\*2.20 ugnen kommer att lanseras under år 2008. \*\*Ugn levererad med gejderkassett, räkna med ett gejderpar mindre.

\*\*\*Ugn kan levereras med annan el-spänning.