

Visual Cooking 2.20

Combi ovens model C-gas / CPE-gas
 Capacity: 20 x 2/1 GN trays or
 40 x 1/1 GN trays



General features

- Natural gas or LPG liquid gas
- Steam technology: injection steam
- Reversible fan ensures perfect roasting and baking
- Adjustable fan speed with 9 steps
- Optional door hinging, left (standard) or right
- Optional distance between runners, 65 mm or 85 mm
- Optional tray size, 2/1 GN (standard) or 1/1 GN trays
- Roll-in trolley with cassette rack
- Easy-to-clean design
- IP X5 protection
- Cabinet and oven chamber in BS 304 S 31 stainless steel
- Rounded corners in oven chamber
- Easily detachable door seal
- Halogen light in oven chamber
- Standard stand
- Timer function with current time, date and timer
- Manual humidity pulsing
- Preheating up to 300°C

General operating modes

- Hot air: 30-250°C
- Steaming with injection steam: 30-120°C
- Cook & Regen: 30-180°C
- Proving: 30-40°C

Scandinavian safety concept

- Oven door with ventilated heat-reflecting glass
- CTD Cool Touch Door (max. outside temperature of 65°C)
- 2-step door handle in stainless steel for optimum safety
- Integrated drip tray in stainless steel, self-emptying
- Automatic door stop at 110° and 180°
- Runners with stop

C-gas ovens standard features

Panel with turn switch and digital display
 Memory of 50 programmes - each with up to 10 steps
 CombiSmart® 10-step humidity control
 Semi-automatic cleaning system
 Automatic cooling
 Error registration system



CPE-gas ovens standard features

Panel with soft keys and TFT display
 Memory of 200 programmes - each with up to 10 steps
 Cook book with 65 preset programmes
 ClimaOptima® automatic humidity control: 70-250°C
 CombiWash® fully automatic cleaning system
 Integrated hand shower
 Manual or automatic cooling
 Automatic service diagnosis system
 HACCP quality control
 USB connection




Optional features (visit www.houno.com)

CombiWash® fully automatic cleaning system (C-gas)
 Integrated hand shower (C-gas)
 Multi-point probe, external location
 Extra multi-point probe (CPE-gas)
 Remote control with CombiNet® (CPE-gas)
 Rack for plates, 99 or 117 plates
 Insulating thermal blanket
 Extra roll-in trolley
 Various voltages
 Extraction hood with or without steam condenser

Visual Cooking 2.20

Combi ovens model C-gas / CPE-gas
Capacity: 20 x 2/1 GN trays or
40 x 1/1 GN trays

Visual Cooking



CAPACITY	
Tray size	2/1 GN or 1/1 GN
Number of runners, 65 mm	20 (40)
Number of runners, 85 mm	15 (30)
Portions	600
Potatoes	160/128 kg
Rice	40 kg
Vegetables	100 kg
Roasts	120-140 kg
Chickens, 900 g	96 pcs.
Rolls	600 pcs.
DIMENSIONS	
OVEN	
Width	1125 mm
Height - table model	-
Height with stand	1855 mm
Depth (excl. handle)	1004 mm
Weight	406 kg

DIMENSIONS		OVEN PACKED
Width		1200 mm
Height - table model		-
Height with stand		1855 mm
Depth (excl. handle)		1000 mm
Weight		421 kg
SPECIFICATIONS		
Voltage		1 NAC 230 V
Gas type		natural gas or LPG liquid gas
Electrical connection		1.9 kW
Gas consumption		54 kW
Fuse protection		13 A
Consumption at max yield		7,4 m3/h natural gas
Consumption at max yield		5,0 kg/h LPG liquid gas
Gas supply connection		3/4" RG outside
Water connection		3/4" RG outside
Drain		Ø 50 mm outside